

PNOZ X8P 230VAC 3n/o 2n/c 2so

777768



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 3 N/O, 2 N/C, 2 semiconductor. Automatic/monitored start UB 230 V AC, width: 45 mm, plug-in terminals of screw type Monitoring E-STOP, safety gates.

Technical details

| | |
|--|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor |
| Operating modes: | Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;Monitored manual reset |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 230,0 |
| Supply voltage type: | AC |
| Terminal style: | Plug-in |
| Terminal type: | Screw terminal |
| Number of instantaneous safety contacts: | 3 |
| Number of delayed safety contacts: | 0 |
| Number of auxiliary contacts: | 2 |
| Number of semiconductor outputs: | 2 |
| Stop category: | 0 |
| Max. current at DC13 I (6 cycles/min): | 7.0 A |
| Max. current at AC15: | 5.0 A |
| Width dimension: | 45.0 mm |
| Height dimension: | 94.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 425 g |

Net weight:

415 g

Ambient temperature:

-10 - 55 °C

Optional accessories



374281

PNOZ X Set plug in screw terminals P3+P4