

PNOZ e5.13p C 24VDC 2so

784191



Safety relay (standalone) Inputs: 1-/2-channel wiring without detection of shorts across contacts Outputs: 2 safety outputs + 1 auxiliary output in semiconductor technology, delayed internal AND operation, automatic/monitored start, UB 24 V DC, Width: 22.5 mm, plug-in spring-loaded terminals, connecting several devices, E-STOP & safety gate monitor, evaluation device safety sensor.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Instantaneous E-STOP monitoring;Limit switch;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Dual-channel;Detection of shorts across contacts;Start-up testing;Monitored manual reset;without detection of shorts across contacts;Self test;with AND input;With OR input
Product standard:	EN 60947-5-1
Standards:	DIN V VDE 801-1/A1;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1;VDE 0116
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal type:	Spring-loaded terminal
Number of instantaneous safety outputs:	2 ST
Number of test pulse outputs:	1
Stop category:	0
Width dimension:	22.5 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	145 g
Net weight:	125 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2