

PNOZ e7p C 24VDC 2 so

784197



Safety relay (standalone) UB 24 V DC, width: 22.5 mm, plug-in terminals of screw type Connecting several devices. For monitoring 2 single beam Light barriers.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Application options:	Instantaneous E-STOP monitoring;Limit switch;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 4;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Detection of shorts across contacts;Monitored manual reset;Self test;with AND input
Product standard:	EN 61496-1
Standards:	DIN V VDE 801-1/A1;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal type:	Spring-loaded terminal
Terminal style:	Plug-in
Number of instantaneous safety outputs:	2 ST
Number of test pulse outputs:	2
Stop category:	0
Width dimension:	22.5 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	145 g
Net weight:	125 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2