

PZE X4.1P C 24VDC 4n/o

787587



Contact expansion Inputs: 2-channel wiring Outputs: 4 N/O UB 24 V DC, width: 22.5 mm, plug-in spring-loaded terminals. Contact block for contact contact expansion in connection with safety-related control components.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Instantaneous contact expansion
Operating modes:	Single-channel;Dual-channel;without detection of shorts across contacts
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	Plug-in
Terminal type:	Spring-loaded terminal
Number of instantaneous safety contacts:	4
Number of delayed safety contacts:	0
Max. current at DC13 I (6 cycles/min):	4.0 A
Voltage at AC15:	230 V
Width dimension:	22.5 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	195 g
Net weight:	185 g
Ambient temperature:	-10 - 55 °C

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2
