

PSWZ X1P C 0,0075-0,5V/24-240VACDC

787951



Safety relay (standalone) Inputs: 1-/2-channel wiring. Outputs: 2 N/O, 1 N/C, 2 semiconductor UB 24 - 240 V AC/DC, UM = 0.0075 - 0.5 V AC/DC. UMmax = 690 V. Width: 45mm, plug-in spring-loaded terminals. Standstill monitor. The device monitors the EMF voltage created when motors run down.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Standstill monitoring |
| Operating modes: | Single-channel;Automatic reset;Dual-channel |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;EN ISO 14119;VDE 0113-1 |
| Supply voltage (V): | 24,0 - 240,0 |
| Supply voltage type: | AC/DC |
| Terminal style: | Plug-in |
| Terminal type: | Spring-loaded terminal |
| Number of semiconductor outputs: | 2 |
| Max. current at DC13 I (6 cycles/min): | 4.0 A |
| Max. current at AC15: | 3.0 A |
| Measuring circuit frequency range: | 0 - 3000 |
| Width dimension: | 45.0 mm |
| Height dimension: | 101.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 330 g |
| Net weight: | 325 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



374291

PNOZ X Set spring loaded terminals P3+P4
