

PMCprotego D.12/00B/0/0/2/208-480VAC

8176542

Technical data at 3 x 400 V AC: Continuous output current: 12 A; I_{max} (5 s) = 24 A; Power consumption in S1 mode: 9 kVA Integral brake resistor
Further hardware options: Expansion card PMCprotego S2.

Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	0 = Without
Continuous output current at 3x480V:	12.0 A
Hardware option 2:	0 = Without
Hardware option 3:	B = PMCprotego S2
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	12.0 A
Continuous output current at 3x400V:	12.0 A
Continuous output current at 3x230V:	12.0 A
Output stage clock frequency:	8 kHz
Peak current:	24.00 A
Peak output current max. 5s:	24.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	70.0 mm
Height dimension:	345.0 mm

Depth dimension:	243.0 mm
Gross weight:	5650 g
Net weight:	4550 g
Ambient temperature:	0 - 40 °C