

PMCprotego D.12/00A/0/P/2/208-480VAC

8176551

Base device with increased peak output current Technical data at 3 x 400 V AC: Continuous output current: 12 A; I_{max} (2 s) = 30 A; I_{max} (5 s) = 24 A; Power consumption in S1 mode: 9 kVA Integral brake resistor Further hardware options: Expansion card PMCprotego S1.

Technical details

| | |
|--------------------------------------|-----------------------|
| Certifications: | CE;EAC (Eurasian);TÜV |
| Hardware option 1: | 0 = Without |
| Continuous output current at 3x480V: | 12.0 A |
| Hardware option 2: | 0 = Without |
| Hardware option 3: | A = PMCprotego S1 |
| Firmware option: | 2 = EtherCat |
| Continuous output current at 3x208V: | 12.0 A |
| Continuous output current at 3x400V: | 12.0 A |
| Continuous output current at 3x230V: | 12.0 A |
| Output stage clock frequency: | 8 kHz |
| Peak current: | 30.00 A |
| Peak output current max. 5s: | 24.00 A |
| Supply voltage 2 (V): | 24 |
| Supply voltage type 2: | DC |
| Number of STO-Enables: | 2 |
| Number of digital inputs: | 4 |
| Number of CANopen interfaces: | 1 |
| Software option: | 2 = Without |
| Width dimension: | 70.0 mm |
| Height dimension: | 345.0 mm |

| | |
|----------------------|-----------|
| Depth dimension: | 243.0 mm |
| Gross weight: | 5650 g |
| Net weight: | 4550 g |
| Ambient temperature: | 0 - 40 °C |