

PMCprotego D.12/100/0/P/2/208-480VAC

8176554



Base device with increased peak output current Technical data at 3 x 400 V AC: Continuous output current: 12 A; I_{max} (2 s) = 30 A; I_{max} (5 s) = 24 A; Power consumption in S1 mode: 9 kVA Integral brake resistor Further hardware options: Expansion card I/O.

Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	1 = I/O expansion
Hardware option 2:	0 = Without
Hardware option 3:	0 = Without
Firmware option:	2 = EtherCat
Supply voltage (V):	208,0 - 480,0
Continuous output current at 3x208V:	12.0 A
Continuous output current at 3x230V:	12.0 A
Continuous output current at 3x400V:	12.0 A
Continuous output current at 3x480V:	12.0 A
Output stage clock frequency:	8 kHz
Peak current:	30.00 A
Peak output current max. 5s:	24.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of analogue inputs:	2
Number of CANopen interfaces:	1
Width dimension:	70.0 mm

Height dimension:	345.0 mm
Depth dimension:	243.0 mm
Gross weight:	5600 g
Net weight:	4500 g
Ambient temperature:	0 - 40 °C