

PMCprotego D.24/00D/0/P/2/208-480VAC

8176575



Basis unit with increased peak output current Technical Details at 3 x 400 V AC supply voltage: Permanent output current: 24 A; I_{max} (2 sec.) = 72 A; I_{max} (5 sec.) = 48 A; Power consumption in S1 operation: 18 kVA Internal brake resistor and mains filter additional hardware option: Expansion Card PMCprotego S2-2

Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	0 = Without
Continuous output current at 3x480V:	24.0 A
Hardware option 2:	0 = Without
Hardware option 3:	D = PMCprotego S2-2
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	24.0 A
Continuous output current at 3x400V:	24.0 A
Continuous output current at 3x230V:	24.0 A
Output stage clock frequency:	8 kHz
Peak current:	72.00 A
Peak output current max. 5s:	48.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	100.0 mm
Height dimension:	348.0 mm

Depth dimension:	243.0 mm
Gross weight:	6950 g
Net weight:	5650 g
Ambient temperature:	0 - 40 °C