

## PMCprotego D.48/A0C/0/0/2/208-480VAC

8176583

Technical data at 3 x 400 V AC: Continuous output current: 48 A; I<sub>max</sub> (5 s) = 96 A; Power consumption in S1 mode: 35 kVA required accessories: Brake resistor 15 Ohm. Further hardware options: Expansion cards PMCprotego S1-2 and PROFINET.

### Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Continuous output current at 3x480V:	48.0 A
Hardware option 2:	0 = Without
Hardware option 3:	C = PMCprotego S1-2
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	48.0 A
Continuous output current at 3x400V:	48.0 A
Continuous output current at 3x230V:	48.0 A
Output stage clock frequency:	8 kHz
Peak current:	96.00 A
Peak output current max. 5s:	96.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	190.0 mm
Height dimension:	386.0 mm
Depth dimension:	244.0 mm

Gross weight:	15750 g
Net weight:	13250 g
Ambient temperature:	0 - 40 °C