

## PMCprotego D.01/20C/0/0/2/208-480VAC

8176600



Technical data at 3 x 400 V AC: Continuous output current: 1.5 A; I<sub>max</sub> (2 s) = 4.5 A; I<sub>max</sub> (5 s) = 3.0 A; Power consumption in S1 mode: 1.1 kVA Integral brake resistor Further hardware options: Expansion card PMCprotego S1-2 Expansion card PROFIBUS-DP slave.

### Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	2 = Profibus
Continuous output current at 3x480V:	1.5 A
Hardware option 2:	0 = Without
Hardware option 3:	C = PMCprotego S1-2
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	2.5 A
Continuous output current at 3x400V:	1.5 A
Continuous output current at 3x230V:	2.0 A
Output stage clock frequency:	8 kHz
Peak current:	4.50 A
Peak output current max. 5s:	3.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	70.0 mm
Height dimension:	345.0 mm

Depth dimension:	243.0 mm
Gross weight:	5700 g
Net weight:	4600 g
Ambient temperature:	0 - 40 °C