

PMCprotego D.06/20C/0/0/2/208-480VAC

8176614



Technical Details at 3 x 400 V AC supply voltage: Permanent output current: 6 A; I_{max} (2 sec.) = 18 A; I_{max} (5 sec.) = 12 A; Power consumption in S1 operation: 4,5 kVA Internal brake resistor and mains filter additional hardware option: Expansion Card Profibus DP Slave and PMCprotego S1-2

Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	2 = Profibus
Continuous output current at 3x480V:	6.0 A
Hardware option 2:	0 = Without
Hardware option 3:	C = PMCprotego S1-2
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	6.0 A
Continuous output current at 3x400V:	6.0 A
Continuous output current at 3x230V:	6.0 A
Output stage clock frequency:	8 kHz
Peak current:	18.00 A
Peak output current max. 5s:	12.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	70.0 mm
Height dimension:	345.0 mm

Depth dimension:	243.0 mm
Gross weight:	5750 g
Net weight:	4650 g
Ambient temperature:	0 - 40 °C