

## PMCprotego D.06/A00/0/0/2/208-480VAC

8176639



Technical data at 3 x 400 V AC: Continuous output current: 6 A; I<sub>max</sub> (2 s) = 18 A; I<sub>max</sub> (5 s) = 12 A; Power consumption in S1 mode: 4.5 kVA Integral brake resistor Further hardware options: Expansion card PROFINET.

### Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 2:	0 = Without
Hardware option 3:	0 = Without
Firmware option:	2 = EtherCat
Supply voltage (V):	208,0 - 480,0
Continuous output current at 3x208V:	6.0 A
Continuous output current at 3x230V:	6.0 A
Continuous output current at 3x400V:	6.0 A
Continuous output current at 3x480V:	6.0 A
Output stage clock frequency:	8 kHz
Peak current:	18.00 A
Peak output current max. 5s:	12.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of analogue inputs:	2
Number of CANopen interfaces:	1
Width dimension:	70.0 mm
Height dimension:	345.0 mm

Depth dimension:	243.0 mm
Gross weight:	5600 g
Net weight:	4500 g
Ambient temperature:	0 - 40 °C