

PMCprotego D.72/03E/0/C/2/208-480VAC

8176780

Technical Details at 3 x 400 V AC supply voltage: Permanent output current: 72 A; I_{max} (5 sec.) = 140 A; Power consumption in S1 operation: 50 kVA necessary accessories: brake resistor 10 OHM Additional options: - coated PCBs -Fan controller, card in Slot 2 -Expansion Card PMCprotego S1-2-C, card in Slot 3

Technical details

Certifications:	CE;EAC (Eurasian);TÜV
Hardware option 1:	0 = Without
Continuous output current at 3x480V:	72.0 A
Firmware option:	2 = EtherCat
Continuous output current at 3x208V:	72.0 A
Continuous output current at 3x400V:	72.0 A
Continuous output current at 3x230V:	72.0 A
Output stage clock frequency:	8 kHz
Peak current:	140.00 A
Peak output current max. 5s:	140.00 A
Supply voltage 2 (V):	24
Supply voltage type 2:	DC
Number of STO-Enables:	2
Number of digital inputs:	4
Number of CANopen interfaces:	1
Software option:	2 = Without
Width dimension:	190.0 mm
Height dimension:	386.0 mm
Depth dimension:	244.0 mm
Gross weight:	15650 g

Net weight:	13150 g
-------------	---------

Ambient temperature:	0 - 40 °C
----------------------	-----------