

PMCProtego D.06/000/0/0/2/110-230VAC

8176813



Technical Details at 3 x 230 V AC supply voltage: Permanent output current: 6,0 A; I_{max} (2 sec.) = 18,0 A; I_{max} (5 sec.) = 12,0 A; Power consumption in S1 operation: 2,3 kVA Internal brake resistor and mains filter

Technical details

| | |
|--------------------------------------|-----------------------|
| Certifications: | CE;EAC (Eurasian);TÜV |
| Hardware option 1: | 0 = Without |
| Hardware option 2: | 0 = Without |
| Hardware option 3: | 0 = Without |
| Firmware option: | 2 = EtherCat |
| Supply voltage (V): | 110,0 - 230,0 |
| Continuous output current at 3x230V: | 6.0 A |
| Output stage clock frequency: | 8 kHz |
| Peak current: | 18.00 A |
| Peak output current max. 5s: | 12.00 A |
| Supply voltage 2 (V): | 24 |
| Supply voltage type 2: | DC |
| Number of STO-Enables: | 2 |
| Number of digital inputs: | 4 |
| Number of analogue inputs: | 2 |
| Number of CANopen interfaces: | 1 |
| Width dimension: | 70.0 mm |
| Height dimension: | 345.0 mm |
| Depth dimension: | 243.0 mm |
| Gross weight: | 5500 g |

| | |
|----------------------|-----------|
| Net weight: | 4400 g |
| Ambient temperature: | 0 - 40 °C |