

PSEN ma1.1p-10/PSEN1.1-10/3mm/1unit

506411



Magnetic safety switch 2 N/O, 4-pin M8 connector, square design IP67, operating distance 3 mm, height design 13 mm PU = 1 sensor with actuator.

Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	M8, 4pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	3.0 mm
Assured release distance:	19.0 mm
Protection type, housing:	IP65;IP67
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	42.8 mm
Depth dimension:	13.0 mm
Gross weight:	45 g
Net weight:	40 g
Ambient temperature:	-25 - 70 °C
Operating modes:	Single connection

Accessories



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m

Optional accessories



380200

PSS67 Cable M8sf M12sm, 3m



380201

PSS67 Cable M8sf M12sm, 5m

380202

PSS67 Cable M8sf M12sm, 10m



380203

PSS67 Cable M8sf M12sm, 30m



380204

PSS67 Cable M8af M12sm, 3m



380205

PSS67 Cable M8af M12sm, 5m



380206

PSS67 Cable M8af M12sm, 10m



380207

PSS67 Cable M8af M12sm, 30m



380300

PSEN ma adapter



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



773600

PDP67 F 8DI ION



540310

PSEN screw M4x16 10pcs
